



Instant and Redundant Emergency Notification

Colleges and universities across the country are relying on **Inova OnAlert™** as part of a multi-modal approach to emergency notification. Inova OnAlert is a real-time visual notification system that displays emergency messages on bright and visible LED signs throughout your campus. When not in use for emergency messaging, Inova OnAlert displays add everyday value by displaying informational messages or the current time and date.

Integrated

Inova OnAlert integrates with virtually any popular mass notification platform. Therefore, an emergency manager can trigger an RSS/XML-based message on the Inova OnAlert signs at the same time that he is sending an emergency email or SMS/text message to any notification technology connected to the centralized system. This ability to distribute messages to multiple end points from one interface saves valuable time during a crisis, when every second counts.

Redundant

Inova OnAlert includes a locally-hosted messaging web site that functions as a backup system in the event of a malfunction in the centralized emergency notification system. It allows authorized emergency managers and IT administrators to override RSS/XML-based messages if necessary. This redundancy offers protection from any single point of failure in the notification technology.

Secure

Inova OnAlert's secure technology allows only authorized users to send RSS/XML-based messages, assuring that designated administrators will always have sole control of emergency messages sent to the signs.

Efficient

Inova OnAlert displays are powered by Power over Ethernet (PoE), a network standard that draws both data and power from a single network connection, so no AC outlets are needed. PoE eliminates the need for wall transformers, allows centralized UPS backup, and is fully compatible with powered and non-powered 10/100BaseT Ethernet devices. Since PoE devices consume significantly less energy than AC-powered devices, they are widely regarded as energy-efficient and environmentally-friendly.

Three Types of Messaging Provide Value

Inova OnAlert LED displays provide value during both emergency and non-emergency situations. Three messaging priority levels are included — time and date, low- and high-priority RSS/XML-based messaging, and administrator override messaging.

Time and Date

When there are no active emergency or informational messages, Inova OnAlert displays can be configured to present time and date information from any network time server. In this way, Inova OnAlert signs offer ROI every day — not just in emergency situations.



RSS/XML-based messaging

Low-priority messaging: Administrators may designate specific low-priority RSS feeds, such as local news or weather, to override the time and date display.



Emergency messaging: In the event of an emergency, Inova OnAlert signs will display emergency messages along with optional audible alerts and **color changes** that demand attention. These messages can be controlled from your centralized notification system.

Administrator Override Messaging

If the centralized notification system is unavailable when you need to send messages to the signs, administrators can simply log on to a locally-hosted messaging website to send override messages. This redundancy ensures that there is no single point of technology failure, and you will always be able to control emergency messages sent to the signs.

Inova OnAlert Specifications

| | | | |
|----------------------------|--|--------------------------|--|
| LED Colors | Three colors (red, yellow, green) | Power | IEEE 802.3af compatible, 15.4 watts max using Power over Ethernet switch |
| LED Size (Diameter) | 0.2" (5 mm) | Agency Approvals | CE Marked |
| LED Spacing (Pitch) | 0.3" (7.6 mm) | Case Material | Black molded plastic over steel frame |
| Character Set | Block (sans serif), Profile (sans serif), upper/lower case | Mounting | Hardware for ceiling mount included. Optional wall, tilt wall or VESA mounts |
| Presentation Modes | Scroll up, Ribbon left | Weight | OAX2: 6 lbs, OAX2E: 7.2 lbs |
| Time and Date | 12/24 hour time formats, Multiple date formats | Dimensions | OAX2: 30.9" x 6.9" x 2.3" OAX2E: 40.5" x 6.9" x 2.3" |
| Computer Interface | TCP/IP connectivity, supports DHCP and static IP addressing, with automatic IP address discovery system, supports SNTP | Hardware Warranty | Three years |
| Special Features | Telnet and SSH for remote diagnostics/firmware upgrades | | |

Note: Specifications and design are subject to change without notice.



1.866.686.8774 | www.inovasolutions.com | info@inovasolutions.com