


Keeping perfect time in sight.

TTSync™ Digital Clocks harmonize the workplace with reliable wireless time keeping, optimum visibility & a variety of size, format & LED color selections.



- Receives a dependable time signal from *TimeTrax™ Sync RF Wireless Transmitter* every 20 seconds to ensure consistently updated time
- Available in 4 digit (HH:MM) or 6 digit (HH:MM:SS) formats to accommodate accurate & detailed time keeping & recording needs
- Vibrant LED display for optimum visibility (typically 250ft viewing distance)
- Variety of clock size, bezel & LED color options to adapt to environment requirements
- Low profile, smooth surface ABS frame with non-glare shatterproof & polycarbonate lens for easy viewing & durability
- Wide range of enhanced viewing & protective accessories including wall & ceiling brackets, wire guards & wash-down enclosures
- Available in 12in flying lead or 6ft cord options
- Automatically adjusts for Daylight Savings Time & power outages for maintenance-free operation



Smart.
scan QR code for
industry solutions

* Digital Clocks also available in
Power Over Ethernet or WiFi Versions
(see PoE Digital or WiFi Digital Clock
smart sheets)





SPECIFICATIONS

| | | |
|--------------------------------|---|--|
| Time Base | Microprocessor | |
| Time Update Frequency | Every 20 seconds | |
| Method | 902-928 MHz frequency-hopping technology | |
| | FLYING LEAD | CORD |
| Power Input | 105/240 VAC or 24/36 VAC/VDC | 105-120 VAC |
| Average Power Consumption | <13W | 20mA |
| Operating Temp | -30°F (-34.44°C) to 130°F (54.44°C) | |
| DISPLAY | | |
| Display Format | 12 or 24 hour mode/date/alt date, time | |
| Digits | 7 segment LED digits | |
| Visibility | 100ft (30.5m) 2.5in digit height 200ft (60.96m) 3in digit height 250ft (76.05m) 4in digit height | |
| Color | ● Red (R) ● Blue (B) ● Green (G) | |
| CASE | | |
| Case | Smooth surface 94VO/5VA ABS | |
| Bezel Color | Black (B) Silver (S) | |
| Lens | Shatterproof, side molded, polished polycarbonate crystal | |
| Mounting | Wall, Dual Wall, Dual Ceiling | |
| Warranty | 3-Year manufacturer's limited warranty | |
| Guarantee | 30-Day money back guarantee | |
| Compliance | FCC part 15 section 15.247 FCC ID# WC7H9ALG1 | |
| CHARACTER HEIGHT/DIGITS | WEIGHT | DIMENSIONS (WXHXD) |
| 2.5in/6-digit HH:MM:SS | 1.5lbs (0.680kg) | 11.25in x 4.5in x 1.5in (28.25cm x 11.5cm x 3.75cm) |
| 3in/4-digit HH:MM | 1.5lbs (0.680kg) | 11.25in x 4.5in x 1.5in (28.25cm x 11.5cm x 3.75cm) |
| 4in/4-digit HH:MM | 1.9lbs (0.861kg) | 11.5in x 6.25in x 1.5in (29cm x 15.75cm x 3.75cm) |
| 4 in/6-digit HH:MM:SS | 2.3lbs (1.043kg) | 15.5in x 6.25in x 1.5in (39cm x 15.75cm x 3.75cm) |
| SHIPPING WEIGHT | FLYING LEAD | CORD |
| 2.5in/6-digit | 1.8lbs (.81kg) | 2.05lbs (.92kg) |
| 3in/4-digit | 1.8lbs (.81kg) | 1.95lbs (.88kg) |
| 4in/4-digit | 2.3lbs (1.04kg) | 2.8lbs (1.27kg) |
| 4in/6-digit | 3.0 lbs (1.3kg) | 3.75lbs (1.7kg) |
| Includes | Security mounting bracket & key, wall mounting template, security mounting bracket template | |

ACCESSORIES

| PART # | DESCRIPTION |
|-------------|--|
| 9T1WI* | Ethernet Wireless RF Transmitter, shelf unit (includes software) |
| S9DSXOLAUB | Ethernet Wireless RF Transmitter, shelf unit (w/o software) |
| S9DWXSLAUB* | Ethernet Wireless RF Transmitter, wall unit (includes software) |
| 42337 | Ethernet Wireless RF Transmitter, wall unit (w/o software) |
| 42321 | Dual Digital Clock Wall Bracket (3x4/2.5x6/4x4) |
| 42422 | Dual Digital Clock Wall Bracket (4x6) |
| 42443 | Analog/Digital dual clock Ceiling Bracket |
| 42316 | 4in x 6 digit Digital Clock Chrome Wire Guard |
| 42400 | 4in x 4 digit Digital Clock Chrome Wire Guard |
| 42401 | 2.5in x 6 digit Digital Clock Chrome Wire Guard |
| 42689 | Digital Clock Wash-Down Enclosure |
| 42281 | Wall Clock Security Mount Replacement Key |
| 42247 | Digital Security Mount Replacement |

*Either part number required for clock operation

